

# POWERCRETER® 20

Does much more than look good on paper.

MAX VOLUME OUTPUT: 17 yd<sup>3</sup>/hr (13m<sup>3</sup>/hr)  
MAX CONCRETE PRESSURE: 2085 psi (144 bar)  
MAX AGGREGATE SIZE: 1" (25mm)  
HORIZONTAL PUMPING DISTANCE: 700' (210m)  
VERTICAL PUMPING DISTANCE: 400' (120m)



ENGINEERED TO REDUCE PULSATION AND NOZZLEMAN FATIGUE WHEN SHOTCRETING, THE VERSATILE POWERCRETER 20 CAN BE FED BY A READY MIX TRUCK, ON-SITE MIXER, OPTIONAL INTEGRATED BATCH MIXER OR CONTINUOUS MIXER. ITS HIGH PRESSURE SWING TUBE PUMP DESIGN HANDLES HARSH MIXES, INCLUDING LOW-CEMENT, LOW MOISTURE, REFRACTORY PUMPING CASTABLES. IDEAL FOR A BROAD RANGE OF PUMPING APPLICATIONS, THE POWERCRETER 20 TURNS PERFORMANCE INTO PROFIT.



[WWW.ALLENTOWNSHOTCRETE.COM/PC20](http://WWW.ALLENTOWNSHOTCRETE.COM/PC20) OR 1-800-553-3414

**Allentown**  
SHOTCRETE TECHNOLOGY  
A Putzmeister COMPANY